

# High Power and Low Power Indoor (3000K)

Available in High Power and Low Power models, these indoor LED tape lights deliver smooth, pixel-free illumination and are ideal for a wide range of lighting fixtures. Built with dense 2219 LED chips and engineered for consistent colour output, both options offer reliable, long-lasting performance.




## FEATURES

- Dense 2219 LEDs per meter for seamless, uniform lighting.
- 3000K warm white with CRI 90+.
- SDCM <3, 1 BIN selection for uniformity.
- Slim 8mm wide PCB for tight spaces.
- IP40 rated for protected indoor environments.
- cULus listed for safety and quality assurance.
- 5-year product warranty.

## APPLICATIONS

- Under Cabinet
- Displays
- Coves
- Wall Grazing
- Architectural Features

| SPECIFICATIONS |                          |  |  |
|----------------|--------------------------|--|--|
| Product Code   |                          | SL-ID-30K-LP-XX-A8<br>[XX: Length in feet; A: 2219 LED; 8: 8mm PCB]<br>Available in 20 or 100 feet;<br>For 20 feet: SL-ID-30K-LP-20-A8;<br>For 100 feet: SL-ID-30K-LP-100-A8 | SL-ID-30K-HP-XX-A8<br>[XX: Length in feet; A: 2219 LED; 8: 8mm PCB]<br>Available in 20 or 100 feet;<br>For 20 feet: SL-ID-30K-HP-20-A8;<br>For 100 feet: SL-ID-30K-HP-100-A8 |
| Electrical     | Input Voltage            | 24V DC   |  |
|                | Power Consumption        | 2.93W/ft (9.6W/m)  | 1.46W/ft (4.8 W/m)   |
|                | Efficacy                 | 102Lm/w  | 110Lm/w  |
| Specs          | Colour Temperature       | 3000K  |  |
|                | Lumen Output             | 300Lm/ft (980Lm/m)   | 160Lm/ft (528Lm/m)   |
|                | Beam Angle               | 140°   |  |
|                | Dimmable                 | Yes (PWM / 0-10V / 1-10V)  |  |
| LED            | Chip Type                | 2219   |  |
|                | CRI                      | 90   |  |
|                | # per metre              | 288  |  |
|                | Binning                  | 1BIN   |  |
|                | SDCM                     | <3   |  |
|                | Lifespan                 | 50,000 Hours   |  |
| Design         | Dimensions (Inches)      | .31" W   |  |
|                | Dimensions (Millimeters) | 8mm W  |  |
|                | Max Length               | 20Ft (6M)  |  |
|                | Custom Cuttable          | 2.19" (55.5mm)   |  |
|                | IP Rating                | IP40   |  |
|                | Approved Location        | Indoor   |  |
| Warranty       |                          | 5 Years  |  |
| Approvals      |                          | cULus  |  |



## ACCESSORIES



**SL-ID-W2BC-72**  
6' Powerfeed



**SL-ID-BWBC-6**  
6" Jumper



**SL-ID-B2BC**  
Splice



**SL-ID-LC**  
L-shaped Connector



**SL-ID-TC**  
T-shaped Connector

## DRIVERS

### Dimmable



**TRE24L40DC**  
Max. recommended load:  
36W; Min. recommended  
load: 8W;  
6.77" x 2.67" x 1.26" (171 x  
68 x 32mm)



**TRE24L96DC**  
Max. recommended load:  
90W; Min. recommended  
load: 8W;  
6.77" x 2.67" x 1.26" (171 x  
68 x 32mm)



**SX-24V-DD-100W**  
Switchex

### Non-Dimmable



**LEDDR-24-120W**  
Indoor/Outdoor driver  
Max. recommended load:  
90W;  
10" x 3 3/8" x 3 3/16" (254  
x 85.7 x 80.9mm)



**PGID2448/  
PGID2496**  
Plug-in Driver

## CONTROLLERS



**CNTRL-0-10V-DIM**  
0/1~10V Dimming  
Controller



**CNTRL-4Z-CCT-RM**  
4 Zone CCT Remote



**CNTRL-4Z-CCT-RWP-WH  
OR  
CNTRL-4Z-CCT-RWP-BK**  
Rotating CCT Scene Remote  
(White or Black)